

FIG.1

1/23




FIG.2




FIG.3

2/23




FIG.4




FIG.5A

3/23




FIG. 5B

4/23




FIG.5C




FIG.6A

5/23




FIG.6B




FIG.6C

6/23




FIG.6D




FIG. 7

7/23




FIG.8

8/23




FIG.9

9/23




FIG.10

10/23




FIG.11

11/23




FIG.12

12/23

COMPARISON OF WASTE WATER FILTRATION SYSTEM
 OF THIS INVENTION WITH CONVENTIONAL APPARATUS

ITEM	PROCESSING ₃ CAPACITY 5m ³ /h	
	CONVENTIONAL APPARATUS	APPARATUS ACCORDING TO INVENTION
WASTE WATER PROCESSING CAPACITY(SS)pH	300mg/L 5-7	900mg/L 3-11
INITIAL COST	1	0.33
POWER CONSUMPTION	23.8kW	5.3kW
RUNNING COST	1	0.2
MAINTENANCE NATURE	ORDINARY	EASY
STRUCTURE	COMPLEX	SIMPLE
QUALITY OF FILTERED WATER	○	○
CATCHABILITY OF SLUDGE	○	○
FILTER	UF MODULE POLYOLEFIN ₂ HIGH POLYMER 2.5kg/cm ² (PRESSURIZED)	POLYOLEFIN ₂ 0.4kg/cm ² (SUCTION)

FIG.13

13/23




FIG.14

14/23




FIG.15

15/23





FIG.16

16/23



17/23




FIG.18A

18/23




FIG.18B




FIG.19




FIG.20




FIG.21

20/23




FIG.22




FIG.23

21/23




FIG.24




FIG.25

22/23




FIG.26A

23/23




FIG. 26B

